

# TROUBLESHOOTING GUIDE

## PRO TWIN FOAMING SYSTEM



SYMPTOM	PROBABLE CAUSE	REMEDY
No flow	<ol style="list-style-type: none"> <li>No water supply.</li> <li>Clogged hydraulic parts</li> </ol>	<ol style="list-style-type: none"> <li>Open the water supply outside tap, select 'product' or 'rinse', turn on the spray gun.</li> <li>Check the water supply filter (input station). Check the venturi.</li> </ol>
Product is not mixed or dosed correctly	<ol style="list-style-type: none"> <li>The foot filter is clogged.</li> <li>The calibration nozzle is clogged.</li> <li>Insufficient water pressure.</li> <li>The chemical product container is empty.</li> <li>The suction hose is not properly connected to the elbow fitting.</li> <li>The suction hose is crimped somewhere.</li> <li>Debris or solids in the venturi</li> </ol>	<ol style="list-style-type: none"> <li>Clean or replace the filter.</li> <li>Clean or replace the nozzle.</li> <li>A minimum pressure of 22PSI is required for correct operation; if the pressure is not correct, contact a plumber.</li> <li>Refill or change the chemical product container.</li> <li>Check that the suction hose is properly connected to the fitting, use a clamp for better grip.</li> <li>Check that the suction hose is properly positioned.</li> <li>Clean with water or compressed air (Warning: do not use tools to remove lime deposits because you can affect the functioning of the venturi; only use anti-lime products)</li> </ol>
Concentration too high	<ol style="list-style-type: none"> <li>The nozzle is not fully inserted or wrong metering tip.</li> </ol>	<ol style="list-style-type: none"> <li>Check that the nozzle is securely plugged into the non-return valve or select a smaller metering tip.</li> </ol>
The chemical product container fills with water	<ol style="list-style-type: none"> <li>The non-return valve is clogged or worn.</li> </ol>	<ol style="list-style-type: none"> <li>Clean or replace the non-return valve.</li> </ol>

